

# VesseLINK™

- Reliable satellite communications for at sea operations
- Providing 100% global coverage you can depend on
- Enabling essential communications for critical operations



VesseLINK utilizing Iridium Certus<sup>SM</sup> gives your critical marine operation global communications coverage. It is the communications solution to depend on for essential communications whenever and wherever you are at sea. Whether you operate a large fleet or a single vessel, this commercialized, military-grade solution is designed to meet your unique challenges through a simple, adaptable and robust design.

VesseLINK on Iridium operates using Iridium Certus<sup>SM</sup> broadband services over a network of 66 satellites that cover 100% of the globe, including deep oceans and the poles. The solution utilizes this robust network service to provide highly reliable, mobile and essential voice, text and web communications.

## MULTI-SERVICES PLATFORM

- IP data sessions up to 700kbps(down)/352kbps (up)
- Streaming up to 256kbps
- 3 high quality voice lines
- Location tracking





## TECHNICAL SPECIFICATIONS

Size	12 in x 9 in x 3 in (30.5 cm x 22.9 cm x 7.6 cm)
Weight	7.2 lb. (3.3 kg)
Power	12 VDC input, 11A max (7A avg.) includes powering external HGA-2 Antenna
Connectors	Front: RJ-45 LAN (3) Class 2 PoE RJ-45 WAN (1) for cellular connection RJ-14 POTS Rear: DC Power Input (10-32V) MIL-STD-1275D DC Power Input, +12V Regulated GPIO (RS-232, +12V out, DISTRESS, Radio Gateway, GPIO) TNC Connector, RF connection to Antenna Wi-Fi reverse SMA SIM slot
Mechanical Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL- STD-810G, Test Method 516.6,

## ANTENNA SPECIFICATIONS

High-gain, electronic phased array antenna to enable the fastest upload and download speeds to cover any vessel communications need from safety services to operational reporting and logging	
Size	14 in x 9 in h (35.6 cm dia. x 22.9 cm h)
Weight	6.2 lb. (2.8 kg)
Power	Directly powered by the terminal at 24 VDC
Operating Temperature	-30 to +55 degrees C
Mechanical Vibration and Shock	MIL-STD-810G, Test Method 514.6, Proc. 1, Category 20, Annex D MIL-STD-810G, Test Method 516.6, Proc. IV
Salt-Fog/Corrosion Standard	IEC 60945, Section Proc. IV

### HEAD OFFICE

MetOcean Telematics  
21 Thornhill Drive  
Dartmouth, Nova Scotia  
Canada B3B 1R9  
sales@metocean.com

+1 902 468 2505

### UNITED STATES

MetOcean Telematics  
1750 Tysons Blvd  
Suite 1500, Office 1547  
McLean, VA 22102  
sales@metocean.com

+1 844 728 2868

### UNITED KINGDOM

MetOcean Telematics  
Hilldale Farm  
Titchfield Lane,  
Wickham, UK PO17 5NZ  
sales@metocean.com

+44 1489 888 555

### CANADA

MetOcean Telematics  
2 Gurdwara Rd Suite 608  
Ottawa, Ontario  
Canada K2E 1A2  
sales@metocean.com

+1 613 702 3196